

SDI INPUT & OUTPUT FORMATS	<p>3G:SMPTE 424M@2.97 and 2.967Gb/s • 1080p@60/59.94/50Hz</p> <p>HD:SMPTE 292M/274M/296M@1.485 and 1.435Gb/s • 1080i@60/59.94/50Hz • 1080p/psf@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25/24/23.98Hz</p> <p>SD:SMPTE 259M@270Mb/s • 625i50 • 525i59.94</p>	LCD / BUTTON MENU OPTIONS	<ul style="list-style-type: none"> • HDMI output type • Output Select • Multi-Viewer Output Format • Multi-Viewer Number of Windows • Multi-Viewer Layout • Multi-Viewer Audio Source • Multi-Viewer Reference • Full Screen is Scaled • Input Routing • GPI mode • Setup
HDMI OUTPUT FORMATS	<ul style="list-style-type: none"> • 1080p@60/59.94/50Hz • 1080i@60/59.94/50Hz • 1080p@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25 • 625i50 • 525i59.94 	INPUTS	<ul style="list-style-type: none"> • 16 x (3G/HD/SD)-SDI • Input Equalization > 100M using Belden 1694A • USB for control and updates
POWER	<ul style="list-style-type: none"> • +5V to +32V DC • Positive Centre Pin 	OUTPUTS	<ul style="list-style-type: none"> • HDMI Type A • 1 x SDI (3G/HD/SD)-SDI
DIMENSIONS	220mm x 103.7mm x 29.5mm (8.7" x 4.1" x 1.2")		